



Kubota
D1105 BG

7,5 kW / 7,5 kVA 8 kW / 8 kVA 230 V 240 V - 50 Hz. 60 Hz	
Round/Min	1500 rpm 1800 rpm
Phase	Single Phase
Cooling Engine	Heat exchanger
Fuel Consumption on Load	3 L/h
Noise level @ 7 mt 61 db(a)	59 db(a)
Dimension (with canopy)	980 x 575 x 675 mm
Weight (with canopy)	331 kg



Kubota
D1703 M BG

12 kW / 12 kVA 13 kW / 13 kVA 230 V 240 V- 50 Hz. 60 Hz	
Round/Min	1500 rpm 1800 rpm
Phase	Single Phase
Cooling Engine	Heat exchanger
Fuel Consumption on Load	4,3 L/h
Noise level @ 7 mt 61 db(a)	59 db(a)
Dimension (with canopy)	1115 x 660 x 710 mm
Weight (with canopy)	427kg



Kubota
V 2203 M BG

16 kW / 16 kVA 17 kW / 17 kVA 230 V 240 V - 50 Hz. 60 Hz	
Round/Min	1500 rpm 1800 rpm
Phase	Single Phase
Cooling Engine	Heat exchanger
Fuel Consumption on Load	5,6 L/h
Noise level @ 7 mt 61 db(a)	59 db(a)
Dimension (with canopy)	1330 x 660 x 710 mm
Weight (with canopy)	481 kg



Kubota
V 2403 M BG

18 kW / 23 kVA 19 kW / 24 kVA 230 V 240 V - 50 Hz. 60 Hz	
Round/Min	1500 rpm 1800 rpm
Phase	Single Phase
Cooling Engine	Heat exchanger
Fuel Consumption on Load	6,2 L/h
Noise level @ 7 mt 61 db(a)	59 db(a)
Dimension (with canopy)	1475 x 695 x 765 mm
Weight (with canopy)	558 kg



Kubota
V 3300 BG

24 kW / 30 kVA 25 kW / 31 kVA 230 V 240 V - 50 Hz. 60 Hz	
Round/Min	1500 rpm 1800 rpm
Phase	Single Phase
Cooling Engine	Heat exchanger
Fuel Consumption on Load	8,4 L/h
Noise level @ 7 mt 61 db(a)	59 db(a)
Dimension (with canopy)	1660 x 740 x 840 mm
Weight (with canopy)	731 kg



Kubota
V 3800 DIT BG

34 kW / 43 kVA 35 kW / 44 kVA 400 V 480 V- 50 Hz. 60 Hz	
Round/Min	1500 rpm 1800 rpm
Phase	Trifaze
Cooling Engine	Heat exchanger
Fuel Consumption on Load	9,4 L/h
Noise level @ 7 mt 61 db(a)	59 db(a)
Dimension (with canopy)	1670 x 750 x 900 mm
Weight (with canopy)	760 kg



Perkins
403D-11G

7,5 kW / 7,5 kVA 8 kW / 8 kVA 230 V 240 V - 50 Hz. 60 Hz	
Round/Min	1500 rpm 1800 rpm
Phase	Single Phase
Cooling Engine	Heat exchanger
Fuel Consumption on Load	2,6 L/h
Noise level @ 7 mt 61 db(a)	58 db(a)
Dimension (with canopy)	980 x 575 x 675 mm
Weight (with canopy)	365 kg



Perkins
403A-15G1

12 kW / 12 kVA 13 kW / 13 kVA 230 V 240 V - 50 Hz. 60 Hz	
Round/Min	1500 rpm 1800 rpm
Phase	Single Phase
Cooling Engine	Heat exchanger
Fuel Consumption on Load	3,7 L/h
Noise level @ 7 mt 61 db(a)	59 db(a)
Dimension (with canopy)	1115 x 660 x 710 mm
Weight (with canopy)	468kg



Perkins
404A-22G1

18 kW / 23 kVA 19 kW / 24 kVA 230 V 240 V - 50 Hz. 60 Hz	
Round/Min	1500 rpm 1800 rpm
Phase	Single Phase
Cooling Engine	Heat exchanger
Fuel Consumption on Load	5,3 L/h
Noise level @ 7 mt 61 db(a)	59 db(a)
Dimension (with canopy)	1475 x 695 x 765 mm
Weight (with canopy)	615 kg



Perkins
404D-22TG

24 kW / 30 kVA 25 kW / 31 kVA 230 V 240 V - 50 Hz. 60 Hz	
Round/Min	1500 rpm 1800 rpm
Phase	Single Phase
Cooling Engine	Heat exchanger
Fuel Consumption on Load	7,1 L/h
Noise level @ 7 mt 61 db(a)	59 db(a)
Dimension (with canopy)	1660 x 740 x 840 mm
Weight (with canopy)	806 kg



Perkins
1103A-33G

28 kW / 35 kVA 35 kW / 44 kVA 230 V 240 V - 50 Hz. 60 Hz	
Round/Min	1500 rpm 1800 rpm
Phase	Trifaze
Cooling Engine	Heat exchanger
Fuel Consumption on Load	8,1 L/h
Noise level @ 7 mt 61 db(a)	59 db(a)
Dimension (with canopy)	1670 x 750 x 900 mm
Weight (with canopy)	830 kg



Perkins
1103A-33TG1

42 kW / 52 kVA 52 kW / 65 kVA 230 V 240 V - 50 Hz. 60 Hz	
Round/Min	1500 rpm 1800 rpm
Phase	Trifaze
Cooling Engine	Heat exchanger
Fuel Consumption on Load	10,8 L/h
Noise level @ 7 mt 61 db(a)	60 db(a)
Dimension (with canopy)	1671 x 750 x 900 mm
Weight (with canopy)	845 kg

KUBOTA JENERATÖRLER

PERKINS JENERATÖRLER

ROTASINDAN VAZGEÇMEYENLERE



İnternet sitemizi
ziyaret etmek için



İMC Jeneratör A.Ş.

imc.gen.tr

+90 322 290 32 90

info@imc.gen.tr

Marine Generator

İMC Jeneratör; kara jeneratörlerindeki 40 yıllık uzmanlığını "marin grubunda" da kullandığı dünya markası ürünlerle, güvenliğinizi ve konforunuzu güvence altına aldı.

- ✓ Benzersiz Kalite
- ✓ Yüksek Performans
- ✓ Uzun Kullanım Ömrü
- ✓ Yüksek Verim
- ✓ Daha Az Yakıt Tüketimi
- ✓ Düşük Egzoz Emisyonu
- ✓ Su Soğutmalı
- ✓ Daha Az Titreşimli
- ✓ Daha Sessiz
- ✓ Daha Kompakt
- ✓ Uzman Teknik Servis
- ✓ Bol ve Kaliteli Yedek Parça
- ✓ 7,5 kw'dan Başlayan Güçlerle



KALİTE STANDARTLARIMIZ VE BELGELERİMİZ



İMC Jeneratör,
ürünlerini aşağıdaki standartlara göre üretir



Marine Generator



imc GENERATORS